



*Soft
Soak*
SpaGuard

Starting Your Spa With The SoftSoak® System

AN AT-A-GLANCE GUIDE

First Time Start-up

1. Fill spa with water.
2. Once spa is filled, start equipment following the manufacturer's directions and heat to operating temperature.
3. Balance spa water with SpaGuard® Total Alkalinity Increaser and Calcium Hardness Increaser. Follow label directions or recommendations from your SpaGuard computerized water analysis.
4. Add the following amounts of SoftSoak® products per 150 gallons of spa water:
 - Add 1 1/2 ounces of SoftSoak Waterline Control
 - Add 1 ounce of SoftSoak Stain & Scale Control
 - Add 3 ounces of SoftSoak Spa ShockCirculate your water continuously for approximately 30 minutes with the blowers off.
5. Add 1 ounce of SoftSoak Sanitizer per 150 gallons of spa water and circulate continuously again for approximately 30 minutes.
6. Using SoftSoak Spa Water Test Strips, check your SoftSoak Sanitizer level and pH. The sanitizer level should be between 30 and 50 ppm and the pH range should be within 7.2 to 7.6.

Weekly Care

1. Using SoftSoak[®] Spa Water Test Strips, test the pH, total alkalinity, calcium hardness and sanitizer levels of your spa. Write down the results.
2. Add the following amounts of SoftSoak products per 150 gallons of spa water:
 - Add 3/4 ounce of SoftSoak Waterline Control
 - Add 1/4 ounce of SoftSoak Stain & Scale Control
 - Add between 1 1/2 to 3 ounces of SoftSoak Spa Shock according to spa use rate. If your spa is used three or more times per week, add 3 ounces per 150 gallons of spa water.
3. The SoftSoak Sanitizer levels should be 30 - 50 ppm. If sanitizer level is 15 - 30 ppm, add 1/2 ounce of SoftSoak Sanitizer per 150 gallon of spa water. If sanitizer level is 0 - 15 ppm, add 1 ounce of SoftSoak Sanitizer per 150 gallons of spa water.
4. If pH is outside 7.2 to 7.6, adjust as needed with Spa Guard pH Increaser or pH Decreaser.

Monthly Care

- Have your water tested by your SoftSoak dealer.
- Chemically clean your filter with SoftSoak[®] Filter Cleaner.

Every 3 To 4 Months

- Drain, clean, polish and refill your spa.



©2003 Bio-Lab, Inc. BioGuard is a registered trademark of Bio-Lab, Inc. Lawrenceville, GA 30049-1002
03-065 12/03

H43238BIOFLY
43238CAR